


UBE

All Electric Injection Molding Machine

UBEMAX **UF** *Universal
Flagship*

Series



UBEMAX UF

Useful & Flexible

The UF Series is a multi-purpose electric machine designed to fit the needs of injection molders worldwide.



UF1600

User Friendly

Easy to Operate and Maintain



UF650W

New e-HUMMA Controller

e-HUMMA offers simple operation for complete utilization

e-HUMMA HUMAN MACHINE Collaborate with Mold-Link

*Mold-Link® is Exclusive to UBE Information System Co.



Main Menu	Injection Profile	Clamp Open / Close Profile
Heat Profile	Statistics Monitor	Overview
Profile Monitor	Maintenance	Memory Storage

[Compact Design Operation Panel]

- *High Resolution large TFT Color Touch Screen with High End Graphics.
- *Accessible Switches provide easy, safe, user friendly operation.

[Main Menu Short Cuts]


- *Quick Access to All Screens from the Main Menu Icons

[Control System]

- *The newly designed control system is capable to add future options at any time with ease.

[CAE Analysis Software (optional item)]

- *Mold-Link® (CAE Analysis Software), exclusively designed by UBE Information System Co., is an interactive software that analyzes actual molding conditions.



Rigid Clamp Design "TAF clamp®"

TAF clamp : Increase Rigidity

60% Deflection Reduction

50% Deflection Reduction

Machine Base Stability Comparison

Platen Deflection Comparison

UBE's proven "Box Sleeve" designed platens have achieved a 60% reduction on platen deflection.

New Advanced Ball Screw Design

Improved ball screw seals reduce grease volume by 90% from conventional design. The improved design also increases durability to enhance ball screw life. Grease distribution control reduces both grease consumption and improves ball screw wear. The new design offers you many competitive advantages, the improved cleanliness of the plant environment along with the reduction of grease usage are only a few.

Ball Screw for Toggle

Distinguished Energy Saving

Recycling energy heat loss which occurs at servo motor's deceleration provides you substantial energy saving.

Accurate and Consistent Injection Process Control "Flex Servo"

UBE's newly developed "Flex Servo" control is based on advanced control logic, therefore achieving a more reliable injection molding process that is both accurate and consistent.

Control Comparison

Electric Power Safety Gate (Optional Item)

UBE UF Series all electric machines offer electric belt driven safety operator gates as an option. When equipped with this option, the cycle time is improved, as well as, safe operating conditions.

Value Added Process Technologies (Optional Item)

Cav-Change®

DIEPREST®

UBE's unique Value Added Technologies such as Cav-Change® & DIEPREST® can be easily added to UF series at any time.

Cav-Change® System

Cav-Change® with DIEPREST® Foam

UBEMAX-UF Series Main Spec Sheet

ITEM		UNIT	UF650W				UF850W				UF1000W				UF1300				
Clamping	Mold Clamping System	—	Double Toggle																
	Mold Clamping Force	kN	6,370																
	Distance Between Tie Bars(H×V)	mm	1,100×1,100																
	Platen Size(H×V)	mm	1,540×1,540																
	Mold Opening Stroke	mm	1,000																
	Mold Height (Min/Max)	mm	400/1,040																
	Daylight	mm	2,040																
	Ejector Force	kN	196																
Ejector Stroke	mm	200																	
Injection	Injection Type	—	i55		i74		i55		i74		i74		i100		i74		i100		
	Screw Type (●:Std)	—	A (●)		B		A (●)		B		A (●)		B		A (●)		B		
	Screw Dia.	mm	90	100	100	112	90	100	100	112	100	112	120	100	112	112	120	120	
	Calculated Injection Volume	cm ³	2,862	3,534	3,927	4,926	2,862	3,534	3,927	4,926	3,927	4,926	5,517	6,333	3,927	4,926	5,517	6,333	
	Injection Weight (PS)	g	2,633	3,251	3,613	4,532	2,633	3,251	3,613	4,532	3,613	4,532	5,076	5,826	3,613	4,532	5,076	5,826	
	Max. Injection Pressure	MPa	185	150	180	150	185	150	180	150	180	150	175	150	180	150	175	150	
	Max. Holding Pressure	MPa	167	135	162	135	167	135	162	135	162	135	158	135	162	135	158	135	
	Injection Rate	cm ³ /s	954	982	1,100	1,182	954	982	1,100	1,182	1,100	1,182	1,477	1,527	1,100	1,182	1,477	1,527	
	Screw Speed	min ⁻¹	165				147				147				130				
	Plasticizing Capacity (PS)	kg/h	445	462	540	560	445	462	540	560	540	560	625	655	540	560	625	655	
	Heater Capacity	kW	39.0				51.0				51.0				54.0				
	Others	Cooling Water Volume	L/min	20×32°C															
Nozzle Center Height (without groud)		mm	1,485																
Machine Size		L	m	10.64		11.08		11.21		11.34		12.08		12.74		12.38		12.94	
		W	m	2.68															
		H	m	2.63															
Machine Weight	ton	44				47				55				58					

ITEM		UNIT	UF1400HW						UF1800						UF3000HW																						
Clamping	Clamping System	—	Double Toggle																																		
	Clamping Force	kN	13,720																																		
	Tie-Bar Space(H×V)	mm	1,830×1,510																																		
	Platen size(H×V)	mm	2,480×1,970																																		
	Clamping Stroke	mm	1,500																																		
	Die Height (Min/Max)	mm	650/1,300																																		
	Daylight	mm	2,800																																		
	Ejector Force	kN	294																																		
Ejector Stroke	mm	250																																			
Injection	Injection Type	—	i74		i100		i128		i128		i161		i200		i161		i200																				
	Screw Type (●:Std)	—	A		B		A (●)		B		A (●)		B		A (●)		B																				
	Screw Dia.	mm	100	112	112	120	120	132	120	132	132	140	140	150	132	140	140	150																			
	Theoretical Injection Volume	cm ³	3,927	4,926	5,517	6,333	6,786	8,211	6,786	8,211	9,032	10,160	10,775	12,370	9,032	10,160	10,775	12,370																			
	Injection Weight (PS)	g	3,613	4,532	5,076	5,826	6,243	7,554	6,243	7,554	8,309	9,347	9,913	11,380	8,309	9,347	9,913	11,380																			
	Max. Injection Pressure	MPa	180	150	175	150	180	150	180	150	175	155	182	155	175	155	182	155																			
	Max. Hold Pressure	MPa	162	135	158	135	162	135	162	135	158	140	164	140	158	140	164	140																			
	Injection Rate	cm ³ /s	1,100	1,182	1,477	1,527	1,493	1,505	1,493	1,505	1,807	2,032	2,031	2,332	1,807	2,032	2,031	2,332																			
	Screw RPM	min ⁻¹	147			130			130			120			110																						
	Plasticating Capacity (PS)	kg/h	540	560	625	655	650	630	650	630	700	680	750	730	700	680	750	730																			
	Heater Capacity	kW	51.0		52.0		54.0		56.0		60.0		60.0		71.0		75.0		80.0																		
	Others	Cooling Water Volume	L/min	20×32°C												30×32°C				30×32°C																	
Nozzle Center Height (without groud)		mm	1,750																																		
Machine Size		L	m	12.56		13.12		13.56		15.28		16.07		16.24		17.24		17.42																			
		W	m	4.10																																	
		H	m	3.10																																	
Machine Weight	ton	85						89						90						180						200						260					

- Re) 1.SI unit is used for the above spec sheet.
 2.Theoretical injection Volume is (Screw Dia. Cross section area) × (Screw stroke)
 3.Injection Volume is calculated for PS, which would be almost 92% of the theoretical injection volume.
 4.Plasticating volume is assumed with PS material.
 5.Max. Injection Pressure and hold pressure might be limited due to the Injection conditions.
 6.These above values are subject to changed without prior notice.



Ultra Large All Electric Injection Molding Machines(1,300t ~ 3,500t)



MD1300HW



UF1600



MD3000HW